

V-Drive Boom Installation Instructions.

The Best Possible way to learn to ski, barefoot and wakeboard!

⚠ WARNING: FAILURE TO ADHERE TO ALL WARNINGS COULD CAUSE DAMAGE TO EQUIPMENT OR VEHICLE, PERSONAL INJURY OR EVEN DEATH. BE AWARE OF YOUR SURROUNDINGS AND ALWAYS STAY CLEAR OF BRIDGES, DOCKS AND ANY OTHER OBSTACLES • DO NOT USE THE BOOM WITHOUT THE CABLES ATTACHED TO THE BOW OF THE BOAT • DO NOT TOW THE BOAT WITH THE BOOM INSTALLED • DO NOT USE TO PULL TUBES, KITES, PARA SAILORS OR STRANDED BOATS • BE SURE TO CHECK ALL HARDWARE, CLAMPS AND CABLES FOR WEAR AND PROPER INSTALLATION PRIOR TO EACH USE.

⚠ WARNING: THE USE OF THIS PRODUCT INVOLVES INHERENT RISKS OF INJURY OR DEATH. TO REDUCE THESE RISKS THE INDIVIDUAL MUST ALWAYS STAY WITHIN THEIR LIMITS AND AT SPEEDS THAT DO NOT EXCEED THEIR LEVEL OF SKILL. THIS PRODUCT IS A TRAINING AID FOR ALL TYPES OF SKIING AND SHOULD ONLY BE USED FOR THAT PURPOSE. DO NOT HANG OFF THE BOOM WHEN THE BOAT IS IN MOTION UNLESS THE INTENT IS TO SKI. THE DRIVER OF THE BOAT SHOULD ALWAYS FOCUS THEIR ATTENTION ON THE SURROUNDINGS, NOT THE SKIER.

1. Read through all directions and warnings completely before installing this product.

Important: The Boom clamp must be installed on the non-tapered portion of the pylon.

Note: For the next step, if your boat has a retractable pylon you must pull up on the pylon and push the clamp body down into the vinyl of the sun deck. The clamp is rounded so it will not damage the vinyl on your boat. You can also cut a hole in a rag and slide it over the pylon before you install the clamp. This will help keep the clamp from rubbing on the vinyl. For questions on this, call us during normal business hours.

2. Attach the V-Drive boom clamp to the pylon using two bolts, washers, spacers, and three main clamp pieces (see illustration for details). Be sure you tighten the bolts evenly, only turning them a couple turns at a time and alternating between them. Don't tighten the bolts completely because you will be adjusting the clamp in a later step.


3. Pin the inside section of the boom to the clamp using the quick release pin.

4. Slide the outside boom section into the inside boom section until the push pin snaps entirely into its hole.

Note: For the next step, the boom should be angled slightly up and forward.

5. Adjust the boom height so it will be positioned chest-high on an average height person when in use.

6. Have someone hold the boom in position at the desired angle. When it's in a suitable position, finish tightening the bolts evenly and firmly.



V-Drive Boom Installation Instructions (continued).

7. Hook the carabineer on the cables to the boat's trailer under-bow eye hook.
- Note:** For the next step, the cables must have no slack hanging down.
8. Pull any slack out of the cables until they are snug. Make sure the cable loop at the end is approximately 1½" - 2" in diameter. Tighten all 8 set screws on the cable clamp with provided allen wrench. Be sure you tighten them until they are extremely tight.
 9. Slide the cable pad over the cables and connect loop strap through the carabineer. Tuck any excess cable back into the cable pad.
 10. The last thing you need to do is attach a section of rope from the boom to the rear of the boat. This keeps the boom from recoiling forward when the skier falls off it. Make sure the rope runs tight up touching the gunnel (see illustration for details).

Boom Removal: Simply unhook the cables from the boat, remove the outside section, disconnect the rope from the rear of the boat, and remove the inside section using the quick release pin. The clamp can remain on the pylon while the boom is not being used.

Tips:

1. To lower the boom for shorter skiers, use the Boom Height Adjuster (part # B107).
2. To help position the skier out of the spray from the boat, use the Boom Extension (part # B110).

